

5"	/	/	
1	3"	3"	
7	115	143	
1	197	219	
11	8"	8"	
1	4'	4'	
NY	8.5" NY	8.5" NY	
11	8"	8"	
0	#10	#10	
)'' )	16"	16"	
G	F/G	F/G	
ISS	Brass	Brass	
8'	5'X8'	6'X10'	

F

E

D

С

В

## **Specifications**

Provide a Fiberglass Reinforced Composite (FRC) Ground set flagpole Model # 25X as manufactured by PLP Composites, Fitzwilliam, NH 03447.

The flagpole shall have a mounting height of 25' and 3' below grade for an overall length of 28'.

The butt diameter shall be 6" and the top diameter 3". The pole weight shall be approximately 59 lbs. and a total shipping weight of 113 lbs.

The flagpole shall be manufactured of fiberglass woven roving and polyester resin with 75% of the reinforcing fibers oriented in the axial plane for maximum stiffness and 25% in the radial plane for required hoop strength. Load calculations shall be based on AASHTO and NAAMM standards with the pole designed with a two to one (2:1) safety factor for 125 mph winds, unflagged, with a 1.3 gust factor.

The flagpole shall have an Entasis taper and shall be void of vertical mold seams.

The flagpole shall be sanded smooth and coated with a high gloss Aliphatic Polyurea coating system which provides extended UV protection and weatherability.

Standard colors include: White, Black, Bronze, Faux-Luminum, & Metallic Bronze



Aeolus Series - Mode	l #25X Standard Fitt	Standard Fittings:		
25' Above Grade Height	6" Gold Anodiz	ed Ball 50' of #10 F	olyester Halyard	
28' Overall Height	Cast FG Statior	nary Truck 16" Flash Co	ollar Location	:
Top Diameter - 3"	1 pair of Brass	Snaps 8.5" Nylon	Cleat	
Butt Diameter - 6"	1 pair of vinyl o	covers 3'x8" Grour	d Sleeve Date:	

**PLP Composites** 

57 Creamery Road - PO Box 429, Fitzwilliam, NH 03447 - Phone: 800-262-6075 - www.plpcomp.com or www.zeusflagpoles.com - info@plpcomp.com